



型號 MODEL	CE10S6AA	CE11S5AA	CE12S5AA	CE1005AA	CE1010AA	
靜摩擦轉距 [kgm](Nm) Static Friction Torque	0.55(5.5)	1.1(11)	2.2(22)	4.5(45)	9(90)	
動摩擦轉距 [kgm](Nm) Dynamic Friction Torque	0.5(5.0)	1.0(10)	2.0(20)	4(40)	8(80)	
功率 Power [24V](W) at 20°C	11	15	20	25	35	
徑方向 Radius	A	63	80	100	125	160
	B	67.5	85	106	133	169
	C	67.5	85	106	133	169
	D	12	15	20	25	30
	E	27.5	31	41	49	65
	F	20	25	30	40	50
	H	24	27	30	33.5	38.9
	L1	46.2	54.2	64.9	75	90.7
	L2	32.2	35.6	40.9	46.8	55.4
	M1	27.1	29.5	34	37.7	43.2
	M2	9.5	20	25	30	38
	P	7.5	11.5	11.6	11.6	14.5
	R	2	2	2	2	3
	T	6	8	10	12	14
a	0.2 (±0.05)			0.3 ($^{+0.05}_{-0.1}$)		
軸方向 Shaft	G1	42.75	55.3	61.75	76.3	98.35
	G2	49.5	63.5	72.5	85	112
	G3	9.5	10.5	11.5	11.4	18.5
	Y1	4.5	5.5	6.5	6.4	8.5
	Y2	12	14	16	16	25
	b	4	5	5	7	7
	t	1.8	2.3	2.3	3.3	3.3
	m	M4*0.7P	M5*0.8P		M6*1P	M8*1.25P
重量 Weight (kg)	0.54	0.95	1.73	3.18	5.6	
保護素子 Protective device	470KD07	GD80KD10		GD80KD14		