



型號 MODEL	PB1S04AA	PB1S051AA	PB1S052AA	PB1S054AA	PB1S059AA	PB1S8AA	PB1S35AA	PB1007AA	PB1014AA	
靜摩擦力 Static Torque Kgm(Nm)	0.04 (0.4)	0.1 (1.0)	0.2 (2.0)	0.45 (4.5)	0.9 (9.0)	1.8 (18)	3.5 (35)	7.2 (72)	14 (140)	
功率 Power [24V] (W)	8	10	11	12	18	24	26	40	50	
徑向尺寸 Radial	A	28	32	40	50	63	80	100	125	160
	B	13.5	15	17	24	27.5	31	41	49	65
	C	11	12.5	19	24	32	38	48.5	58	75
	D	-	-	-	26	35	42	52	62	80
	E	33.5	38	47	58	72	90	112	137	175
	F	39	45	54	65	80	100	125	150	190
	G	4-3.4	4-3.4	4-3.4	4-3.4	4-4.5	4-5.5	4-6.5	4-6.5	4-9.0
軸向尺寸 Axial	M	1-M3	1-M3	1-M4	1-M4	2-M5	2-M5	2-M6	2-M6	2-M8
	N	19.5	21.5	22.5	28.5	26.8	29.9	33.9	37.8	42.6
	O	2	2	2	2	3	3	4	5	6
	P	-	-	-	1.8	2	2	2.5	3.5	3.5
	Q	2.2	2.1	2.7	3	4	4.5	6.4	7.2	9.4
	R	10.5	12	12	14	15	16.5	19	23	26
	S	0.15~0.20	0.15~.20	0.15~0.25	0.25~0.35	0.25~0.35	0.25~0.35	0.25~0.35	0.40~0.50	0.75~0.85
	T	7	10	12	12	15	20	25	30	38
	U	5	8	9.5	9	11.5	16	20	24	31
V	2.5	4	4	5	6	8	10	12	14	
鍵槽 Keyway	W	2	2	3	5	6	6	8	7	10
	X	1	1	1.4	2.3	2.8	2.8	3.3	3.3	3.8
孔徑 Bore	d	6	6	10	15	18	20	30	30	40