



型號 MODEL	PB2S04AA	PB20S1AA	PB20S2AA	PB20S4AA	PB20S9AA	PB21S8AA	PB23S5AA	PB2007AA	PB2014AA	
靜摩擦力 Static Torque Kgm (Nm)	0.04 (0.4)	0.1 (1.0)	0.2 (2.2)	0.45 (4.5)	0.9 (9.0)	1.8 (18)	3.5 (35)	7.2 (72)	14 (140)	
功率 Power [24V] (W)	8	10	11	12	18	24	26	40	50	
徑向尺寸 Radial	A	28	32	40	50	63	80	100	125	160
	C	11	12.5	19	24	32	38	48.5	58	75
	D	-	-	-	26	35	42	52	62	80
	E	33.5	38	47	58	72	90	112	137	175
	F	39	45	54	65	80	100	125	150	190
	G	4-3.4	4-3.4	4-3.4	4-3.4	4-4.5	4-5.5	4-6.5	4-6.5	4-9.0
軸向尺寸 Axial	M	1-M3	1-M3	1-M4	1-M4	2-M5	2-M5	2-M6	2-M6	2-M8
	N	19.5	21.5	22.5	28.5	26.8	29.9	33.9	37.8	42.6
	O	2	2	2	2	3	3	4	5	6
	P	-	-	-	1.8	2	2	2.5	3.5	3.5
	Q	2.2	2.1	2.7	3	4	4.5	6.4	7.2	9.4
	R	10.5	12	12	14	15	16.5	19	23	26
	S	0.15~0.20	0.15~.20	0.15~0.25	0.25~0.35	0.25~0.35	0.25~0.35	0.25~0.35	0.40~0.50	0.75~0.85
	T	7	10	12	12	15	20	25	30	38
	U	16.8	15.8	15.8	22.7	19.4	18.8	20.6	21.4	21.8
V	2.5	4	4	5	6	8	10	12	14	
鍵槽 Keyway	W	2	2	3	5	6	6	8	7	10
	X	1	1	1.4	2.3	2.8	2.8	3.3	3.3	3.8
孔徑 Bore	d	6	6	10	15	18	20	30	30	40